



EFL30 PRO

4-WHEEL LI-ION COUNTERBALANCE FORKLIFT 3.0T

 3000 kg
  6000 mm
  80 V Li-Ion



Built to perform across diverse environments, the EFL Pro Series excels in warehouses, factories, logistics centers, ports, and construction yards. Its high ground clearance, large tires and IPX4 water resistance enable operation on uneven outdoor terrain, while its compact turning radius and quiet, emission-free power make it ideal for indoor use as well. Designed to replace traditional diesel forklifts, the EFL Pro provides high performance with reduced operating costs

SPECIFICATION	REF	UNIT	VALUE
Battery type			Li-Ion
Battery nominal capacity		Ah	80V280AH
Battery voltage		V	80
Load capacity	Q	kg	3000
Load centre distance	c	mm	500
Service weight		kg	4800
Retracted mast height	h_1	mm	2065
Lift height	h_3	mm	3000
Height, mast extended	h_4	mm	4130
Overall length		mm	3627
Overall width	b_1/b_2	mm	1210
Length to face of forks	l2	mm	2557
Fork dimensions	s/e/l	mm	45×122×1070
Turning radius		Wa	2352
Manufacturer			EP
Model designation			EFL 30 PRO

Features

Unmatched Performance and great operator experience

Powered by a 17kW AC driving motor and 30kW PMS pump motor system, the EFL PRO achieves performance, gradeability and residual capacity in line with the best electric forklift with the advantage of the high ground clearance, the big size tires and robust chassis.

EFL PRO hydraulic system feature:

- Full-proportion solenoid valve for a more accurate micro-control
- PMS pump motor and screw type pump for precise and silent hydraulic operation
- Big diameter hydraulic tubing for high oil flow also on the attachments



Sleek Appearance with Enhanced Versatility

The EFL PRO Series combines a sleek, fully-molded design with outstanding stability, thanks to its extended 1753 mm wheelbase. Despite its robust stance, key dimensions—such as width and turning radius—remain comparable to standard electric forklifts, ensuring versatility in any application. Modern LED lighting enhances visibility and reinforces its contemporary look, while the electric parking brake and automatic stop on ramp further elevate safety and control

State of the art controls on the armrest

Multiple functions are integrated at the palm-size end including: forward/reverse, gear switch, lifting/lowering, tilting, sideshift and 4th way, automatic fork leveling button, horn, clamp interlock button, 5th way button switch, turning light switch, sStorage box and USB port, emergency switch





Informative and Multi-functional Full-touch Display

The new OLED touchscreen display provides real-time monitoring of all key forklift operating parameters, including battery state of charge, driving speed, travel direction, wheel angle, and mast tilt angle. Optional functions such as lift height and load weight indicators can also be integrated. Thanks to its touch interface, the operator can easily control all auxiliary systems, including the lighting system, wipers, and cabin heater.

Ergonomic Cabin for Fatigue-free and Convenient Operation

The EFL PRO's ergonomic design begins the moment the operator steps aboard, thanks to the largest access step in its class. Once inside, the EFL PRO features a offering a spacious driving area with a standard suspended seat with armrest. A reduced-size steering wheel, a hydraulic accumulator to prevent kickback, a tempered glass roof for enhanced visibility, and practical storage compartments further elevate the operator experience. For ease of service, power and auxiliary controllers are housed in a protected area accessible through removable panels.



Revolutionary Li-ion Battery and Charging System

At the core of the EFL PRO Series is EP's breakthrough Li-ion technology — a new Li-ion battery system composed of three independent battery modules operating in series to achieve 80V. Each module functions autonomously, ensuring consistent performance and enhanced reliability. This battery architecture enables power from 280Ah to 628Ah, allowing the EFL PRO to adapt its endurance to a wide range of applications. Additionally, each battery module can be repaired or replaced individually, eliminating the costly full-pack replacements typically required when single cells fail. For further charging convenience, both integrated charging and external charging port are available on one truck making EFL PRO flexible for all kinds of applications needs.



Complete configuration including Telematic and innovative options

EFL PRO comes standard with telematic system that allows to manage the fleet and the rental activities in an effective and efficient manner. The system tracks data for truck and battery usage, like uptime, battery status and real-time location. It allows users to monitor and analyze assets conditions, providing remote diagnostics and improving the efficiency of fleet management. Another standard feature of the EFL PRO is the ergonomic armrest equipped with fingertip or joystick controls including load-leveling function activated at the press of a single button.

The following items are available as optional equipment:

Full cabin with integrated heater on the dashboard; Load height indicator; Load weight indicator; 360°Panorama System with human recognition and collision warning (no CE); Panoramic OHG with glass roof (no CE); Turn speed control; Ambient-noise Adaptive Buzzer



VDI Chart

	SPECIFICATION	REF	UNIT	VALUE
1.1	Manufacturer			EP
1.2	Model designation			EFL 30 PRO
1.3	Drive			Electric
1.4	Operator type			Seated
1.5	Load capacity	Q	kg	3000
1.6	Load centre distance	c	mm	500
1.8	Load distance, centre of drive axle to fork		mm	481
1.9	Wheelbase		mm	1753
2.1	Service weight		kg	4800
2.2	Axle loading, laden front/rear		kg	6923/873
2.3	Axle loading, unladen front/rear		kg	2234/2566
3.1	Tyre type			Pneumatic
3.2	Tyre size, front		mm	28X9-15-14PR
3.3	Tyre size, rear		mm	6.50-10-10PR
3.4	Additional wheels (castor wheels)		mm	2x/ 2
3.5	Wheels, number front/rear (x=drive wheels)			2x/ 2
3.6.1	Tread width, front	b ₁₀	mm	1010
3.7.1	Tread width, rear	b ₁₁	mm	980


	SPECIFICATION	REF	UNIT	VALUE
4.0	Max lift height	H	mm	6000
4.1	Tilt of mast/fork carriage forward/backward		°	6/6
4.12	Tow coupling height		mm	510
4.19	Overall length		mm	3627
4.2	Retracted mast height	h_1	mm	2065
4.20	Length to face of forks	l2	mm	2557
4.21	Overall width	b_1/b_2	mm	1210
4.22	Fork dimensions	s/e/l	mm	45×122×1070
4.23	A,B Fork carriage class/type A, B			3A
4.24	Fork carriage width		mm	1100
4.3	Free lift		mm	135
4.31	Ground clearance, laden, below mast		mm	130
4.32	Ground clearance, centre of wheelbase		mm	165
4.34.1	Aisle width for pallets 1000×1200 crossways		Ast	4033
4.34.2	Aisle width for pallets 800×1200 lengthways		Ast	4233
4.35	Turning radius		Wa	2352
4.4	Lift height	h_3	mm	3000
4.5	Height, mast extended	h_4	mm	4130
4.7	Height of overhead guard (cabin)		mm	2170
4.8	Seat height/standing height		mm	1138
5.1	Travel speed, laden/unladen		km/h	19/20
5.10	Service brake			Hydraulic
5.11	Parking brake			Electromagnetic
5.2	Lifting speed, laden/unladen		m/s	0.55/0.58
5.3	Lowering speed, laden/unladen		m/s	0.43/0.44
5.5	Drawbar pull, laden/unladen			5924
5.6	Max. drawbar pull, laden/unladen			22350
5.8	Max. gradeability, laden/unladen		%	22/28
6.1	Drive motor rating S2 60 min		kW	17
6.2	Lift motor rating at S3 15%		kW	30
6.4	Battery nominal capacity		Ah	80V280AH
6.4	Battery voltage		V	80
6.4.1	Battery type			Li-Ion
6.5	Battery weight		kg	184
6.6	Energy consumption according to DIN EN 16796		kWh/h	8.75



	SPECIFICATION	REF	UNIT	VALUE
6.7	Turnover output according to VDI 2198			180
6.8	Turnover efficiency according to VDI 2198			23.26
8.1	Type of drive control			AC
10.1	Operating pressure for attachments		bar	180
10.2	Oil volume for attachments		ℓ/min	35
10.5	Steering design			Hydraulic
10.7	Sound pressure level at the drivers ear		dB(A)	< 70

VDI Drawing

EFL 30 PRO

RATED CAPACITIES GRAPH





Mast Options

MAST TYPE	LIFT HEIGHT (H3, MM)	MAST LOWERED HEIGHT (H1, MM)	MAST EXTENDED HEIGHT, NO BACKREST (H4, MM)	MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM)	FREE LIFT HEIGHT, NO BACKREST (H2, MM)	FREE LIFT HEIGHT, WITH BACKREST (H2, MM)	FORWARD TILT (A, DEG)	BACKWARD TILT (B, MM)	LOAD DISTANCE (X, KG)
2-Standard Mast	2700	1915	3365	3830	135	135	6	6	481
2-Standard Mast	3000	2065	3665	4130	135	135	6	6	481
2-Standard Mast	3300	2215	3965	4430	135	135	6	6	481
2-Standard Mast	3500	2315	4165	4630	135	135	6	6	481
2-Standard Mast	3600	2365	4265	4730	135	135	6	6	481

MAST TYPE	LIFT HEIGHT (H3, MM)	MAST LOWERED HEIGHT (H1, MM)	MAST EXTENDED HEIGHT, NO BACKREST (H4, MM)	MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM)	FREE LIFT HEIGHT, NO BACKREST (H2, MM)	FREE LIFT HEIGHT, WITH BACKREST (H2, MM)	FORWARD TILT (A, DEG)	BACKWARD TILT (B, MM)	LOAD DISTANCE (X, KG)
2-Standard Mast	4000	2615	4665	5130	135	135	6	6	481
2-Standard Mast	4500	2865	5165	5630	135	135	6	6	481
2-Free Mast	3000	2090	3715	4175	1455	995	6	6	481
2-Free Mast	3300	2195	4015	4475	1560	1100	6	6	481
2-Free Mast	3600	2345	4315	4775	1710	1250	6	6	481
3-Free Mast	4300	2080	5030	5435	1390	985	6	6	492
3-Free Mast	4500	2160	5270	5675	1470	1065	6	6	492
3-Free Mast	4800	2265	5570	5975	1575	1170	6	6	492
3-Free Mast	5000	2350	5720	6125	1660	1255	6	6	492
3-Free Mast	5500	2600	6220	6625	1910	1505	6	6	492
3-Free Mast	6000	2850	6720	7125	2160	1755	6	6	492

Options

ITEM	OPTIONS (optional items marked in yellow)
Fork dimension	122*45*1070 122*45*1150 122*45*1220 122*45*1370 122*45*1520
Seat type	Comfortable + safety belt switch (41) Suspension seat with armrest and safety belt swich GRAMMER-MSG65
Attachments	Built-in sideshifter External shifter Fork positionr with sideshift External shifter with adjustable forks Clamp
Traction pin	Yes and not customized
Electrostatic chain	Yes and not customized
Front wheel material	Pneumatic Normal solid Traceless solid
Rear wheel material	Pneumatic Normal solid Traceless solid
Battery capacity	80V280AH 80V560AH 80V628AH (NON-CE)
Charger	80V65A (NON-CE) 80V60 (CE) 80V35A Integrated 80V60A Integrated 80V130A 80V150A 80V200A (560/628AH)
Battery display indicator (BDI)	With time (Bluetooth)

ITEM	OPTIONS (optional items marked in yellow)
Area warning lamp	No Both sides Both sides and rear
Rearview mirror	One in front Two on sides and one in front
Buzzer	Regular buzzer Ambient-noise adaptive buzzer (NON-CE)
OPS system	Yes and not customized
USB interface	Cigarette lighter+USB with A and C type
Telematics	Yes and not customized No
Front lamp	LED
Rear lamp	No LED
Warning lamp	Yes and not customized
Steering lamp	LED
Blue lamp	No Rear Front and rear
Cabin	No Basic semi-cabin Upgraded semi-cabin Full cabin
Overhead guard	Strip glass with anti-explosion film Panoramic glass roof (NON-CE)
Clamp interlock	No Yes and not customized
Special AUS/NZ options	No Yes and not customized
Turn speed control	Yes and not customized No
Heating system during lithium battery charging	No Yes and not customized
Operator identification device	No Card reader
Lifting electronic limit	No Yes and not customized
Hydraulic control	Joystick fingertip
Rear armrest horn	Yes and not customized
Area Speed Limit System	No Yes and not customized
Weighing system	No Yes and not customized
Automatic fork leveling	No Yes and not customized
Wiper water unit	Yes only with Cabin
Automatic Parking Brake	Yes and not customized
Height display+Forward tilt speed limit+High-position lateral shift speed control	No Yes and not customized
Surround View System+Human recognition system	No Yes and not customized (NON-CE)